

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 7785-2 (1976): Elevated type aerodrome lighting fittings, Part 2: Fixed focus high intensity bi-directional runway edge lighting fittings [ETD 24: Illumination Engineering and Luminaries]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



IS : 7785 (Part II) - 1976

Indian Standard

SPECIFICATION FOR ELEVATED TYPE
AERODROME LIGHTING FITTINGS

PART II FIXED FOCUS HIGH INTENSITY BIDIRECTIONAL
RUNWAY EDGE LIGHTING FITTINGS

UDC 628.971.8 : 656.71.055.971



© Copyright 1976

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Price Rs 5.00

Gr 2

November 1976

*Indian Standard***SPECIFICATION FOR ELEVATED TYPE
AERODROME LIGHTING FITTINGS****PART II FIXED FOCUS HIGH INTENSITY BIDIRECTIONAL
RUNWAY EDGE LIGHTING FITTINGS**

Illuminating Engineering Sectional Committee, ETDC 45

Chairman

SHRI V. A. KRISHNAMURTHY

Representing

Central Public Works Department, New Delhi

*Members*SURVEYOR OF WORKS III (ELECT) (*Alternate* to

Shri V. A. Krishnamurthy)

SHRI P. K. BANDYOPADHYAY

Philips India Ltd, Bombay

SHRI S. ROYCHOUDHARY (*Alternate*)

WG CDR H. S. BHATIA

Directorate of Technical Development & Production
(Air) (Ministry of Defence)SHRI N. C. GUHA (*Alternate*)

SHRI G. BHATTACHARYYA

National Test House, Calcutta

SHRI D. S. DOSHI

Bajaj Electricals Ltd, Bombay

SHRI JAGDISH SHARAN (*Alternate*)

SHRI K. L. GARG

Directorate General of Supplies & Disposals, New
DelhiSHRI J. S. PASSI (*Alternate*)

SHRI M. P. GUPTA

Crompton Greaves Ltd, Bombay; and Indian
Engineering Association, CalcuttaSHRI S. F. MEHTA (*Alternate*)

SHRI G. S. CHANDRASEKHAR

Crompton Greaves Ltd, Bombay
Indian Engineering Association, Calcutta.(*Alternate*)

SHRI T. S. KUMAR

Central Mining Research Station (CSIR), Dhanbad

SHRI U. S. NIGAM (*Alternate*)

SHRI B. H. MHATRE

Bombay Electric Supply & Transport Undertaking,
BombaySHRI AVTAR SINGH (*Alternate*)

SHRI K. N. NADGIR

Engineer-in-Chief's Branch, Army Headquarters

MAJ J. K. SONI (*Alternate*)

SHRI J. R. PARI

General Electric Co of India Ltd, Calcutta

SHRI S. K. NEOGI (*Alternate*)

(Continued on page 2)

© Copyright 1976

INDIAN STANDARDS INSTITUTION

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS : 7785 (Part II) - 1976

(Continued from page 1)

Members

SHRI K. S. SARMA

SHRI I. P. SINGH

SHRI M. S. ARORA (Alternate)

SHRI H. SINHA

SHRI K. K. ROHATGI (Alternate)

SHRI P. R. SURENDRANATHAN

SHRI S. PURUSHOTTAM (Alternate)

SHRI S. P. SACHDEV,

Director (Elec tech)

Representing

National Physical Laboratory (CSIR), New Delhi
Railway Board (Ministry of Railways)

Illuminating Engineering Society of India, Calcutta

Central Labour Institute, Bombay

Director General, ISI (Ex-officio Member)

Secretary

SHRI A. K. GOGIA

Assistant Director (Elec tech), ISI

Panel for Aviation Lighting Fittings, ETDC 45 : P3

Convener

SHRI R. C. REKHI

Central Public Works Department, New Delhi

Members

SHRI F. ALVARES

SHRI P. K. BANDYOPADHYAY

SHRI S. ROYCHOUDHARY (Alternate)

Wg CDR H. S. BHATTIA

AMA Private Ltd, Bombay

Phillips India Ltd, Bombay

Directorate of Technical Development & Production
(Air) (Ministry of Defence)

Paisa Fund Glass Works, Pune

Pradip Lamp Works, Calcutta

National Physical Laboratory (CSIR), New Delhi

Civil Aviation Department, New Delhi

International Airports Authority of India, New
Delhi

SHRI P. R. KIBE

SHRI K. K. ROHATGI

SHRI K. S. SARMA

SHRI S. VENKASWAMY

MAJ V. C. VERMA

Indian Standard

SPECIFICATION FOR ELEVATED TYPE AERODROME LIGHTING FITTINGS

PART II FIXED FOCUS HIGH INTENSITY BIDIRECTIONAL RUNWAY EDGE LIGHTING FITTINGS

0. FOREWORD

0.1 This Indian Standard (Part II) was adopted by the Indian Standards Institution on 20 August 1976, after the draft finalized by the Illuminating Engineering Sectional Committee had been approved by the Electrotechnical Division Council.

0.2 This standard is intended to deal with specific requirements of the elevated type fixed focus high intensity bidirectional runway edge lighting fittings, in order to ensure their safe performance, good construction and high class of workmanship.

0.3 This standard (Part II) is one of the series of Indian Standards on elevated type aerodrome lighting fittings. This standard shall be read in conjunction with IS : 7785 (Part I)-1975*.

0.4 In preparing this standard, assistance has been derived from the following:

International Standards and Recommended Practices: Aerodromes Annex-14-1971. Ed 6. International Civil Aviation Organization.

Specification No. 1258-1-(1969) Specification for aviation lighting fittings. Department of Transport (Air Services), Canada.

Advisory Circular No. 150/5345-20-1967 Specification for L-802 Runway and strip light. Federal Aviation Administration (USA).

Advisory Circular No. 150/5345-9C-1969 Specification for L-819 Fixed focus bidirectional high intensity fittings. Federal Aviation Administration (USA).

Advisory Circular No. 150/4345-26A-1971 FAA-L-823 Plug and receptacles, cable connectors. Federal Aviation Administration (USA).

Military Specification MIL-C-25050A (ASG)-1963 General requirement for colors, aeronautical lights and lighting equipment. Federal Aviation Administration (USA).

*Specification for elevated type aerodrome lighting fittings: Part I General requirements,

IS : 7785 (Part II) - 1976

0.5 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test, shall be rounded off in accordance with IS : 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard (Part II) covers the specific requirements for the elevated type fixed focus high intensity bidirectional runway edge lighting fittings.

2. TERMINOLOGY

2.1 For the purpose of this standard, the definitions given in IS : 1885 (Part XVI/Sec 1)-1968† and IS : 1885 (Part XVI/Sec 2)-1968‡ shall apply.

3. CONDITIONS OF USE

3.1 In additions to conditions specified in **3.1** and **3.2** of IS : 7785 (Part I)-1975§, the lighting fitting shall be designed to withstand the blast effects from jet engines including wind velocities up to 560 km/h.

3.2 The fittings shall be suitable for use on systems with a voltage not greater than 250 V rms to earth.

4. DETAILED REQUIREMENTS

4.1 The lighting fitting shall consist of the optical system with filters/shields as may be required. It shall also include a housing, leads, breakable coupling(s), base plate with pipe column/stake, as may be required. They shall conform to IS : 7785 (Part I)-1975§.

4.2 The fitting shall be suitably designed for housing a maximum of 210 W 6.6 A lamp, so as to serve as a high intensity lighting fitting [see Indian Standard 'Specification for lamps for aerodrome lighting fittings' (under preparation)].

4.3 The lighting fitting shall be supplied with a clear lens/filter, when it is intended for runway edge lighting.

*Rules for rounding off numerical values (revised).

†Electrotechnical vocabulary: Part XVI Lighting, Section 1 General aspects.

‡Electrotechnical vocabulary: Part XVI Lighting, Section 2 General illumination lighting fittings and lighting for traffic and signalling.

§Specification for elevated type aerodrome lighting fittings: Part I General requirements,

4.4 When used as a threshold lighting fitting, it shall be supplied with 180° green lens/filter and 180° red lens/filter for the optical system.

4.5 The provision of filter (180°/360°) shield and its colour shall be agreed between the purchaser and the supplier.

4.6 The light distribution shall be tested with a clear lens and a 210 W 6·6 A lamp operated at or corrected to 4 500 lumens fitted to the runway edge lighting fittings. The light distribution shall be in accordance with or excess of values of candela specified in 4.7 to 4.10.

4.7 The light distribution shall be asymmetrical with front and rear beam having an elevation of 4·5° and a toe-in-angle of 3·5° (the corresponding longitudinal angles are 86·5° and 273·5°). The 90° to 270° horizontal line is parallel to the runway centre line and the 0° horizontal direction is toward and perpendicular to the runway centre line.

4.8 The minimum light intensity in the beam shall be 20 000 candela in the rectangular beam of 5° horizontal and 4° vertical with rounded corners of 2° radii at 20 000 candela and 5 000 candela in 10° horizontal and 9° vertical with rounded corners of 4° radii.

4.9 The beam axis shall be within 1·5° of the 4·5° elevation and the 3·5° toe-in-angles when the light has been properly levelled and correctly aimed.

4.10 The light shall have a minimum of 400 candela from 92° to 268° horizontal at elevations of 4·5° to 12·5° vertical for circling guidance.

4.11 The maximum for a runway light shall be 100 candela from 320° to 40° horizontal at elevations of 0° to 15° vertical. It shall have a maximum of 50 000 candela in the main beam.

4.12 In all areas not otherwise specified, the minimum shall be 20 candela in all directions above the horizontal.

4.13 Where colour is specified, the candela values shall not be less than those obtained by multiplying the candela values specified above by the following:

Yellow	0·400
Green	0·150
Red	0·150

5. MARKING

5.1 Information to be Marked — Each light fitting shall be suitably and clearly marked with the following information:

- Manufacturer's name or, trade-mark or both;
- Model or type designation; and
- Country of manufacture.

5.2 Method of Marking — Marking shall be legible and indelible and shall be made either on the fitting itself or on a name plate securely fixed thereto.

NOTE — The performance of marking is checked by inspection or by rubbing lightly with a piece of cloth, or by both methods.

5.3 A complete list of parts and installation instructions shall be furnished with each fittings. Sufficient drawings or instructions shall be provided to indicate clearly the method of installation.

5.4 The fittings may also be marked with the ISI Certification Mark.

NOTE — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. The ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

6. TESTS

6.1 Classification of Tests

6.1.1 Type Tests — The following shall constitute type tests:

- a) Photometric test (*see 6.2*),
- b) Test for resistance to heat (*see 6.3*),
- c) Test for temperature shock (*see 6.4*),
- d) Test for bubble obstruction (*see 6.5*),
- e) Rain-proof test (*see 6.6*),
- f) Insulation resistance (dry) test (*see 6.7*),
- g) High voltage test (*see 6.8*), and
- h) Test for mechanical strength (*see 6.9*).

6.1.2 Acceptance Tests — The following shall be carried out as acceptance tests:

- a) Test for bubble obstruction (*see 6.5*),
- b) Rain-proof test (*see 6.6*),
- c) Insulation resistance (dry) test (*see 6.7*), and
- d) High voltage test (*see 6.8*).

6.1.3 Routine Tests — The insulation resistance (dry) test (*see 6.7*) and high voltage test (*see 6.8*) shall be carried out as routine tests,

6.2 Photometric Test — The provisions of 5.8.2 of IS : 7785 (Part I)-1975* shall apply.

6.3 Test for Resistance to Heat — The provisions of 5.8.3 of IS : 7785 (Part I)-1975* shall apply.

6.4 Test for Temperature Shock — The provisions of 5.8.4 of IS : 7785 (Part I)-1975* shall apply.

6.5 Test for Bubble Obstruction — The provisions of 5.1.7 of IS : 7785 (Part I)-1975* shall apply.

6.6 Rain-Proof Test — The provisions of 5.8.6 of IS : 7785 (Part I)-1975* shall apply.

6.7 Insulation Resistance (Dry) Test — The provisions of 5.8.7 of IS : 7785 (Part I)-1975* shall apply.

6.8 High Voltage Test — The provisions of 5.8.8 of IS : 7785 (Part I)-1975* shall apply.

6.9 Test for Mechanical Strength — The provisions of 5.8.9 of IS : 7785 (Part I)-1975* shall apply.

*Specification for elevated type aerodrome lighting fittings: Part I General requirements.

INDIAN STANDARDS
ON
ILLUMINATING ENGINEERING

IS :

- 1777-1961 Industrial lighting fittings with metal reflectors
- 1885 (Part XVI/Sec 1)-1968 Electrotechnical vocabulary: Part XVI Lighting, Section 1
General aspects
- 1885 (Part XVI/Sec 2)-1968 Electrotechnical vocabulary: Part XVI Lighting, Section 2
General illumination, lighting fittings and lighting for traffic and signalling
- 1913-1969 General and safety requirements for electric lighting fittings (*first revision*)
- 1944-1970 Code of practice for lighting of public thoroughfares
- 1947-1961 Flood lights
- 2149-1970 Luminaires for street lighting (*first revision*)
- 2206 (Part I)-1962 Flameproof electric lighting fittings: Part I Well-glass and bulkhead
types
- 2206 (Part II)-1976 Flameproof electric lighting fittings: Part II Fittings using glass tubes
- 2493-1963 Well-glass lighting fittings for use underground in mines (non-flameproof type)
- 2672-1966 Code of practice for library lighting
- 3287-1965 Industrial lighting fittings with plastic reflectors
- 3528-1966 Waterproof electric lighting fittings
- 3553-1966 Watertight electric lighting fittings
- 3646 (Part I)-1966 Code of practice for interior illumination: Part I Principles for good
lighting and aspects of design
- 3646 (Part II)-1966 Code of practice for interior illumination: Part II Schedule for
values of illumination and glare index
- 3646 (Part III)-1968 Code of practice for interior illumination: Part III Calculation of
coefficients of utilization by the BZ method
- 4012-1967 Dust-proof electric lighting fittings
- 4013-1967 Dust-tight electric lighting fittings
- 4347-1967 Code of practice for hospital lighting
- 5077-1969 Decorative lighting outfits
- 6585-1972 Screwless terminal and electrical connections for lighting fittings
- 6665-1972 Code of practice for industrial lighting
- 7537-1974 Road traffic signals
- 7569-1975 Cast acrylic sheets for use in luminaires
- 7678-1975 Method of photometric testing of incandescent type luminaires for general
lighting service
- 7785 (Part I)-1975 Elevated type aerodrome lighting fittings: Part I General
requirements
- 7785 (Part II)-1976 Elevated type aerodrome lighting fittings: Part II Fixed focus high
intensity bidirectional runway edge lighting fittings
- 7785 (Part III)-1976 Elevated type aerodrome lighting fittings: Part III Omni-directional
runway edge lighting fittings
- 8030-1976 Luminaires for hospitals

PUBLICATIONS OF INDIAN STANDARDS INSTITUTION

INDIAN STANDARDS

Over 8 500 Indian Standards covering various subjects have been issued so far. Of these, the standards belonging to the Electrotechnical Group fall under the following categories:

Acoustics and acoustical measurement	Instrument transformers
Automobile electrical equipment	Insulating materials
Batteries	Insulators and accessories
Cinematographic equipment	Integrating meters
Conductors and cables	Lamps and lamp accessories
Domestic electrical appliances	Lifts and escalators
Electric welding equipment	Lightning arresters
Electrical installations, codes of practice	Motors and generators
Electrical instruments	Nomenclature and symbols
Electron tubes and valves	Power capacitors
Electronic components	Power converters
Electronic equipment	Relays
Environmental testing procedures	Rotating machinery
Fans	Semiconductor devices
Flameproof electrical equipment	Switchgear and controlgear
High voltage techniques	Transformers and reactors
Illuminating engineering	Winding wires
	Wiring accessories
	Unclassified

OTHER PUBLICATIONS

ISI Bulletin (Published Every Month)					
Single Copy	Rs 4 ⁰⁰
Annual Subscription	Rs 38 ⁰⁰
Standards : Monthly Additions					
Single Copy	Rs 0 ³⁰
Annual Subscription	Rs 3 ⁰⁰
Annual Reports (from 1948-49 Onwards)	Rs 2 ⁰⁰ to 6 ⁰⁰
ISI Handbook, 1975	Rs 30 ⁰⁰

INDIAN STANDARDS INSTITUTION

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephone : 27 01 31 (20 lines)

Telegrams : Manaksanstha

Regional Offices:

Western : Novelty Chambers, Grant Road
 Eastern : 5 Chowringhee Approach
 Southern : C.I.T. Campus, Adyar

Telephone
 BOMBAY 400007 37 97 29
 CALCUTTA 700072 23 08 02
 MADRAS 600020 41 24 42

Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur
 'F' Block, Unity Bldg, Narasimharaja Square
 Ahimsa Bldg, SCO 82-83, Sector 17C
 5-B-56/57 Nampally Station Road
 117/418 B Sarvodaya Nagar
 B.C.I. Bldg (3rd Floor), Gandhi Maidan East
 Hantex Bldg, (2nd Floor), Rly Station Road

AHMADABAD 380001 2 03 91
 BANGALORE 560002 2 76 49
 CHANDIGARH 160017 2 83 20
 HYDERABAD 500001 4 57 11
 KANPUR 208005 82 72
 PATNA 800004 6 36 55
 TRIVANDRUM 695001 32 27